

Bon Jour Ø 145

03.2005.01 - White


Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	1085
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	57
Beam angle C90-270 (°)	57



Beam Angle: 57°		
h(m)	E(lx)	D(m)
1	1099	1.10
2	275	2.19
3	122	3.29
4	69	4.38
5	44	5.48

Luminous flux luminaire
1085 lm

Electrical


Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	205
Weight (kg)	1.11

Note

Pre-installation frame must be ordered separately



Bon Jour Ø 145



Pre-installation frame
08.8975.00



Honeycomb and cross screening
cylinder
08.8980.14



Decorative screening accessory
08.8979.00



Decorative screening accessory
08.8977.00



Decorative screening accessory
08.8978.00