

03.2008.14.DA - Black


Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	501
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	56
Beam angle C90-270 (°)	56



Luminous flux luminaire
501 lm

Beam Angle:	56°	
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	697	1.06
2	174	2.11
3	77	3.17
4	44	4.23
5	28	5.28

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		

Emergency

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	205
Weight (kg)	1.11

Note

Pre-installation frame must be ordered separately

Bon Jour Ø 145 Dali



Decorative screening accessory
08.8977.00

Decorative screening accessory
08.8979.00

Pre-installation frame
08.8975.00



Honeycomb and cross screening
cylinder
08.8980.14

Decorative screening accessory
08.8978.00