


## Bon Jour Ø 45 Dali

03.2006.01.DA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included. It is necessary to anticipate a space for accessing the driver.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 392                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 6W    | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Spot      |
| <b>Beam angle (°)</b>         | 25        |
| <b>Beam angle C90-270 (°)</b> | 25        |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1772  | 0.45 |
| 2    | 443   | 0.89 |
| 3    | 197   | 1.34 |
| 4    | 111   | 1.79 |
| 5    | 71    | 2.23 |

Luminous flux luminaire  
392 lm

### Electrical

|                       |   |                         |         |
|-----------------------|---|-------------------------|---------|
| <b>Frequency (Hz)</b> | 50/60   | <b>Emergency</b>        | Without |
| <b>Voltage (V)</b>    | 220.00  | <b>Insulation class</b> | II      |
| <b>Dimmable</b>       | Yes   |                         |         |
| <b>Driver</b>         | Remote excluded   |                         |         |
| <b>Driver type</b>    | Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                         |         |

### Physical

|                            |       |
|----------------------------|-------|
| <b>Color</b>               | White |
| <b>Orientation</b>         | Fixed |
| <b>Recessed depth (mm)</b> | 67    |
| <b>Weight (kg)</b>         | 0.13  |

### Note

Accessories included (honeycomb and cross screening cylinder). Remote power supply to be installed in an accessible place.

