


Bon Jour Ø 90 Dali

■ 03.2007.CU.DA - Copper

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	655
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	35
Beam angle C90-270 (°)	35



Beam Angle:	35°		
h(m)	E(lx)	D(m)	
1	1495	0.63	
2	374	1.26	
3	166	1.89	
4	93	2.52	
5	60	3.14	

Luminous flux luminaire
655 lm

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		

Physical

Color	Copper
Orientation	Fixed
Recessed depth (mm)	155
Weight (kg)	0.53

Note

Pre-installation frame must be ordered separately



Bon Jour Ø 90 Dali



Pre-installation frame
08.8974.00

Honeycomb and cross screening
cylinder
08.8976.14