







# Certification / Marking













03.2001.14.DA - Black

 $Recessed\ luminaire\ with\ LED\ light\ source.\ Remote\ 220/240V\ power\ supply\ included.\ It\ is\ necessary\ to\ anticipate\ a$ space for accessing the driver.

### Main specifications

| Number of heads | 1     |
|-----------------|-------|
| Lamp category   | LED   |
| Power (W)       | 6W    |
| CCT (K)         | 2700K |
| CRI             | 90    |
|                 |       |


Net lumen (lm) 352 Mountings

Ceiling recessed Environment

Indoor

### Optical

| Lighting type          | Direct    |
|------------------------|-----------|
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 23        |
| Beam angle C90-270 (°) | 23        |
|                        |           |



Insulation class

Beam Angle: 23° h(m) = E(Ix)D(m) 1739 0.41 2 0.83 435 3 193 1.24 4 109 1.66 5 70 2.07

| Luminous flux lum |
|-------------------|
| 352 lm            |
|                   |

### Electrical

| rrequency (Hz) | 50/60   |
|----------------|---------|
| Voltage (V)    | 220.00  |
| Dimmable       | Yes     |
| Driver         | Remote  |
| Emergency      | Without |

# Physical

| Color               | Black |
|---------------------|-------|
| Orientation         | Fixed |
| Recessed depth (mm) | 67    |
| Weight (kg)         | 0.13  |

## Note

Accessories included (honeycomb and cross screening cylinder). Remote power supply to be installed in an accesible place.