




C1 Double Spot Wall Large Ø 56

■ 03.1243.DR - Anthracite

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed...

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed in an accessible location.




Main specifications

| | | | |
|-----------------------|-------|--------------------|---------------------|
| Lamp category | LED | Mountings | Wall |
| Power (W) | 28W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |
| Net lumen (lm) | 2132 | | |

Optical

| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 45 |
| Beam angle C90-270 (°) | 13 |



| | | |
|-------------|------|------------|
| Beam Angle: | 45° | |
| | h(m) | E(lx) D(m) |
| 1 | 2186 | 0.84 |
| 2 | 546 | 1.68 |
| 3 | 243 | 2.52 |
| 4 | 136 | 3.35 |
| 5 | 87 | 4.19 |

Luminous flux luminaire
2132 lm

Electrical

| | |
|-------------------------|-----------------|
| Current (mA) | 1200 |
| Dimmable | Yes |
| Driver | Remote excluded |
| Emergency | Without |
| Insulation class | III |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | Anthracite | Spot diameter (mm) | 56 |
| Orientation | Adjustable | | |
| Weight (kg) | 0.96 | | |
| Tilt (°) | 60 | | |
| Rotation (°) | 180 | | |

Note

Preliminary photometries.


C1 Double Spot Wall Large Ø 56



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207

Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch
60.9276

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W
60.9186

Casambi Controller 220-240V. Remote Installation
60.9392

No Trim installation frame for wall mounting.
08.0226.00



Continuous current power supply, 0/1-
10V dimmable, 220/240V – 50/60Hz,
300mA-16W / 350mA-18W / 400mA-21W
/ 500mA-27W / 600mA-32W / 650mA-
35W /
700/750/800/900/950/1000/1050mA-36W
60.9439

Aluminum Mount for Surface Flush
Installation (wall) Double
08.0254.00