




C1 Double Spot Wall Large Ø 56

03.1245.DY - White

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed...

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed in an accessible location.




Main specifications

Lamp category	LED	Mountings	Wall
Power (W)	28W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	2139		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	13



Beam Angle:	14°	
	h(m)	E(lx) D(m)
1	15301	0.24
2	3825	0.48
3	1701	0.72
4	956	0.96
5	612	1.20

Luminous flux luminaire
2139 lm

Electrical

Current (mA)	1200
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White	Spot diameter (mm)	56
Orientation	Adjustable		
Weight (kg)	0.96		
Tilt (°)	60		
Rotation (°)	180		

Note

Preliminary photometries.


C1 Double Spot Wall Large Ø 56




Continuous current power supply
220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W
/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162

Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186

Casambi Controller 220-240V. Remote
Installation
60.9392



Ø82




No Trim installation frame for wall
mounting.
08.0226.00

Continuous current power supply, 0/1-
10V dimmable, 220/240V – 50/60Hz,
300mA-16W / 350mA-18W / 400mA-21W
/ 500mA-27W / 600mA-32W / 650mA-
35W /
700/750/800/900/950/1000/1050mA-36W
60.9439

Aluminum Mount for Surface Flush
Installation (wall) Double
08.0254.00



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207

Continuous current power supply of
20-40W, 110/240V – 50/60Hz. Power
current selected through adjustable
350mA-18,5W / 400mA-21W / 500mA-
26,5W / 600mA-31,5W / 650mA-34,5W /
700mA-37W / 750mA-39,5W /
800/850/900/950/1000/1050/1200 mA-
40W switch
60.9276