




## C1 Double Spot Wall Large Ø 56

03.1248.DY - White

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed...

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed in an accessible location.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Wall
<b>Power (W)</b>	28W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	2216		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	45
<b>Beam angle C90-270 (°)</b>	13



Beam Angle:	45°	
	h(m)	E(lx) D(m)
1	2358	0.84
2	589	1.68
3	261	2.52
4	146	3.35
5	95	4.19

Luminous flux luminaire  
2216 lm

### Electrical

<b>Current (mA)</b>	1200
<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	56
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.96		
<b>Tilt (°)</b>	60		
<b>Rotation (°)</b>	180		

### Note

Preliminary photometries.


## C1 Double Spot Wall Large Ø 56



Continuous current power supply  
220/240V – 50/60Hz. Adjustable Current  
300mA-13W / 350mA-15W / 400mA-18W  
/ 450mA-20W / 500mA-22W / 550mA-  
24W / 600mA-27W / 650mA-29W /  
700mA-31W / 750mA-32W / 800mA-33W  
/ 850mA-35W / 900mA-38W / 950mA-  
40W / 1000/1050mA-42W  
60.9162

Continuous current supply source 240V  
– 50/60Hz with dimmable DALI 2, push  
dimming. 300mA-16W / 350mA-18W /  
400mA-21W / 500mA-27W / 600mA-32W  
/ 650mA-35W  
700/750/800/900/950/1000/1050mA-38W  
60.9186

Casambi Controller 220-240V. Remote  
Installation  
60.9392



Ø82



No Trim installation frame for wall  
mounting.  
08.0226.00

Continuous current power supply, 0/1-  
10V dimmable, 220/240V – 50/60Hz,  
300mA-16W / 350mA-18W / 400mA-21W  
/ 500mA-27W / 600mA-32W / 650mA-  
35W /  
700/750/800/900/950/1000/1050mA-36W  
60.9439

Aluminum Mount for Surface Flush  
Installation (wall) Double  
08.0254.00



---

Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/750/800/900/1000/1050mA – 38W  
60.9207

---

Continuous current power supply of  
20-40W, 110/240V – 50/60Hz. Power  
current selected through adjustable  
350mA-18,5W / 400mA-21W / 500mA-  
26,5W / 600mA-31,5W / 650mA-34,5W /  
700mA-37W / 750mA-39,5W /  
800/850/900/950/1000/1050/1200 mA-  
40W switch  
60.9276