


C1 Double Spot Wall Small Ø 35

03.1210.DY - White



Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed...

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed in an accessible location.




Main specifications

Lamp category	LED	Mountings	Wall
Power (W)	12W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	753		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	14



Beam Angle:	15°	
	h(m)	E(lx) D(m)
1	4140	0.26
2	1035	0.51
3	460	0.77
4	259	1.03
5	166	1.28

Luminous flux luminaire
753 lm

Electrical

Current (mA)	500
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III


Physical

Color	White	Spot diameter (mm)	35
Orientation	Adjustable		
Weight (kg)	0.35		
Tilt (°)	60		
Rotation (°)	180		

Note

Preliminary photometries.

C1 Double Spot Wall Small Ø 35



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207

No Trim installation frame for wall mounting
08.0227.00

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable
60.9592



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186

Aluminum Mount for Surface Flush Installation (wall) Double
08.0255.00

Coated aluminum mount for surface installation (wall)
08.0228.DY



Coated aluminum mount for surface
installation (wall)

08.0228.DR