


## C1 Double Spot Wall Small Ø 35

### ■ 03.1215.DR - Anthracite



Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed...

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories included (up diffuser). The remote power supply (not included) must be placed in an accessible location.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Wall
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	763		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15
<b>Beam angle C90-270 (°)</b>	14



Beam Angle: 15°		
h(m)	E(lx)	D(m)
1	4198	0.26
2	1049	0.51
3	466	0.77
4	263	1.03
5	168	1.28

Luminous flux luminaire  
763 lm

### Electrical

<b>Current (mA)</b>	500
<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Anthracite	<b>Spot diameter (mm)</b>	35
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.35		
<b>Tilt (°)</b>	60		
<b>Rotation (°)</b>	180		

### Note

Preliminary photometries.

## C1 Double Spot Wall Small Ø 35



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/950/1000/1050/1200mA – 38W  
60.9207



No Trim installation frame for wall mounting  
08.0227.00



Coated aluminum mount for surface installation (wall)  
08.0228.DY



Coated aluminum mount for surface installation (wall)  
08.0228.DR



Aluminum Mount for Surface Flush Installation (wall) Double  
08.0255.00