



C1 Double Spot Wall Small Ø 35

03.1216.DY - White

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories integrated (up diffuser). The remote power supply (not included) must be placed...


Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. Accessories integrated (up diffuser). The remote power supply (not included) must be placed in an accessible location.

Main specifications

Lamp category	LED	Mountings	Wall
Power (W)	12W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	755		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	18
Beam angle C90-270 (°)	14



Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2678	0.32
2	669	0.65
3	298	0.97
4	168	1.30
5	107	1.62

Luminous flux luminaire
755 lm

Electrical



Current (mA)	500
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White	Spot diameter (mm)	35
Orientation	Adjustable		
Weight (kg)	0.35		
Tilt (°)	60		
Rotation (°)	180		

Note

Photometric data without up diffuser.



C1 Double Spot Wall Small Ø 35



Aluminum Mount for Surface Flush
Installation (wall) Double
08.0255.00



Coated aluminum mount for surface
installation (wall)
08.0228.ES



Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power current selected
through adjustable switch. 350mA –
15W / 400mA – 17W / 450mA – 19W /
500mA – 22W / 550mA – 24W / 600mA –
26W / 650mA – 28W / 700mA – 30W no
regulable
60.9592



Coated aluminum mount for surface
installation (wall)
08.0228.ER



Coated aluminum mount for surface
installation (wall)
08.0228.EQ



ø82
⚡

No Trim installation frame for wall
mounting
08.0227.00



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207



Coated aluminum mount for surface
installation (wall)
08.0228.DR



Coated aluminum mount for surface
installation (wall)
08.0228.DY