


## C1 Mono Spot Ceiling Large Ø 56

03.1250.DY - White



Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling
<b>Power (W)</b>	14W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	1070		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	14
<b>Beam angle C90-270 (°)</b>	14



<b>Beam Angle:</b>	14°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	15302	0.24	
2	3825	0.48	
3	1700	0.72	
4	956	0.96	
5	612	1.20	

Luminous flux luminaire  
1070 lm

### Electrical

<b>Current (mA)</b>	1200
<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	56
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.46		
<b>Tilt (°)</b>	60		
<b>Rotation (°)</b>	355		

### Note

Preliminary photometries.

## C1 Mono Spot Ceiling Large Ø 56



---

Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W  
60.9186



---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W  
60.9439



---

Casambi Controller 220-240V. Remote Installation  
60.9392



---

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W  
60.9162



---

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



---

Coated aluminum mount for surface installation (ceiling)  
08.0212.DR



Ø82  
⚡



---

Continuous current power supply of  
20-40W, 110/240V – 50/60Hz. Power  
current selected through adjustable  
350mA-18,5W / 400mA-21W / 500mA-  
26,5W / 600mA-31,5W / 650mA-34,5W /  
700mA-37W / 750mA-39,5W /  
800/850/900/950/1000/1050/1200 mA-  
40W switch  
60.9276

---

No Trim installation frame for ceiling  
mounting  
08.0207.00

---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.DY