



C1 Mono Spot Ceiling Large Ø 56

03.1256.DY - White



Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.




Main specifications

Lamp category	LED	Mountings	Ceiling
Power (W)	14W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1158		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle:	23°		
h(m)	E(lx)	D(m)	
1	8468	0.40	
2	2117	0.80	
3	941	1.20	
4	529	1.60	
5	339	2.00	

Luminous flux luminaire
1158 lm

Electrical

Current (mA)	1200
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III


Physical

Color	White	Spot diameter (mm)	56
Orientation	Adjustable		
Weight (kg)	0.46		
Tilt (°)	60		
Rotation (°)	355		

C1 Mono Spot Ceiling Large Ø 56



Coated aluminum mount for surface installation (ceiling)
08.0212.ER



Coated aluminum mount for surface installation (ceiling)
08.0212.EQ



No Trim installation frame for ceiling mounting
08.0207.00



Coated aluminum mount for surface installation (ceiling)
08.0212.DY



Coated aluminum mount for surface installation (ceiling)
08.0212.DR



Continuous current power supply
220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W
/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207



Coated aluminum mount for surface installation (ceiling)
08.0212.ES

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W
60.9439



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W
60.9186

Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch
60.9276



Casambi Controller 220-240V. Remote Installation
60.9392