

## C1 Mono Spot Ceiling Large Ø 56

### ■ 03.1257.DR - Anthracite



Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.


Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

### Main specifications

|                       |       |                    |                     |
|-----------------------|-------|--------------------|---------------------|
| <b>Lamp category</b>  | LED   | <b>Mountings</b>   | Ceiling             |
| <b>Power (W)</b>      | 14W   | <b>Environment</b> | Indoor dry location |
| <b>CCT (K)</b>        | 3000K |                    |                     |
| <b>CRI</b>            | 90    |                    |                     |
| <b>Net lumen (lm)</b> | 1081  |                    |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Flood     |
| <b>Beam angle (°)</b>         | 34        |
| <b>Beam angle C90-270 (°)</b> | 34        |



Beam Angle: 34°

h(m) E(lx) D(m)

1 3687 0.61

2 922 1.22

3 410 1.83

4 230 2.43

5 147 3.04



Luminous flux luminaire  
1081 lm

### Electrical

|                         |                 |
|-------------------------|-----------------|
| <b>Current (mA)</b>     | 1200            |
| <b>Dimmable</b>         | Yes             |
| <b>Driver</b>           | Remote excluded |
| <b>Emergency</b>        | Without         |
| <b>Insulation class</b> | III             |

### Physical

|                     |            |                           |    |
|---------------------|------------|---------------------------|----|
| <b>Color</b>        | Anthracite | <b>Spot diameter (mm)</b> | 56 |
| <b>Orientation</b>  | Adjustable |                           |    |
| <b>Weight (kg)</b>  | 0.46       |                           |    |
| <b>Tilt (°)</b>     | 60         |                           |    |
| <b>Rotation (°)</b> | 355        |                           |    |



## C1 Mono Spot Ceiling Large Ø 56



Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch  
60.9276

Casambi Controller 220-240V. Remote Installation  
60.9392

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W  
60.9439

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W  
60.9162

No Trim installation frame for ceiling mounting  
08.0207.00




---

Continuous current supply source 240V  
– 50/60Hz with dimmable DALI 2, push  
dimming. 300mA-16W / 350mA-18W /  
400mA-21W / 500mA-27W / 600mA-32W  
/ 650mA-35W  
700/750/800/900/950/1000/1050mA-38W  
60.9186





---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.ER




---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.DY




---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.EQ




---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.DR




---

Coated aluminum mount for surface  
installation (ceiling)  
08.0212.ES