



C1 Mono Spot Ceiling Small Ø 35

03.1221.DR - Anthracite



Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.




Main specifications

Lamp category	LED	Mountings	Ceiling
Power (W)	6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	368		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	18
Beam angle C90-270 (°)	18



Beam Angle:	18°		
h(m)	E(lx)	D(m)	
1	2640	0.32	
2	660	0.65	
3	293	0.97	
4	165	1.30	
5	106	1.62	

Luminous flux luminaire
368 lm


Electrical

Current (mA)	500
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Anthracite	Spot diameter (mm)	35
Orientation	Adjustable		
Weight (kg)	0.18		
Tilt (°)	60		
Rotation (°)	355		

C1 Mono Spot Ceiling Small Ø 35



Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186

No Trim installation frame for ceiling
mounting
08.0208.00

Coated aluminum mount for surface
installation (ceiling)
08.0211.EQ



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power current selected
through adjustable switch. 350mA –
15W / 400mA – 17W / 450mA – 19W /
500mA – 22W / 550mA – 24W / 600mA –
26W / 650mA – 28W / 700mA – 30W no
regulable
60.9592

Coated aluminum mount for surface
installation (ceiling)
08.0211.ES

Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207



Coated aluminum mount for surface
installation (ceiling)
08.0211.DR



Coated aluminum mount for surface
installation (ceiling)
08.0211.DY



Coated aluminum mount for surface
installation (ceiling)
08.0211.ER