

C1 Mono Spot Ceiling Small Ø 35

■ 03.1226.DY - White



Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.


Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Main specifications

Lamp category	LED	Mountings	Ceiling
Power (W)	6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	374		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	18
Beam angle C90-270 (°)	18



Beam Angle: 18°

h(m) E(lx) D(m)

1 2678 0.32

2 669 0.65

3 298 0.97

4 167 1.30

5 107 1.62



Luminous flux luminaire
374 lm

Electrical

Current (mA)	500
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White	Spot diameter (mm)	35
Orientation	Adjustable		
Weight (kg)	0.18		
Tilt (°)	60		
Rotation (°)	355		



C1 Mono Spot Ceiling Small Ø 35



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable
60.9592



Coated aluminum mount for surface installation (ceiling)
08.0211.ES



Coated aluminum mount for surface installation (ceiling)
08.0211.DR



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W
60.9186



Coated aluminum mount for surface installation (ceiling)
08.0211.ER



Coated aluminum mount for surface
installation (ceiling)
08.0211.DY



Coated aluminum mount for surface
installation (ceiling)
08.0211.EQ



No Trim installation frame for ceiling
mounting
08.0208.00