

C1 Mono Spot Wall Large Ø 56

03.1231.DY - White

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.


Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Main specifications

Lamp category	LED	Mountings	Wall
Power (W)	14W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	1094		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	7998	0.40
2	1999	0.80
3	889	1.20
4	500	1.60
5	320	2.00

Luminous flux luminaire
1094 lm

Electrical

Current (mA)	1200
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White	Spot diameter (mm)	56
Orientation	Adjustable		
Weight (kg)	0.67		
Tilt (°)	60		
Rotation (°)	180		

C1 Mono Spot Wall Large Ø 56




No Trim installation frame for wall mounting.
08.0205.00



Aluminum Mount for Surface Flush Installation (wall)
08.0210.00



Continuous current power supply
220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W
/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162



Casambi Controller 220-240V. Remote Installation
60.9392



Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186



Continuous current power supply, 0/1-
10V dimmable, 220/240V – 50/60Hz,
300mA-16W / 350mA-18W / 400mA-21W
/ 500mA-27W / 600mA-32W / 650mA-
35W /
700/750/800/900/950/1000/1050mA-36W
60.9439



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207



Continuous current power supply of
20-40W, 110/240V – 50/60Hz. Power
current selected through adjustable
350mA-18,5W / 400mA-21W / 500mA-
26,5W / 600mA-31,5W / 650mA-34,5W /
700mA-37W / 750mA-39,5W /
800/850/900/950/1000/1050/1200 mA-
40W switch
60.9276