


C1 Mono Spot Wall Small Ø 35

■ 03.1201.DR - Anthracite



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.




Main specifications

Lamp category	LED	Mountings	Wall
Power (W)	6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	368		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	18
Beam angle C90-270 (°)	18



Luminous flux luminaire
368 lm

Electrical

Current (mA)	500
Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Anthracite	Spot diameter (mm)	35
Orientation	Adjustable		
Weight (kg)	0.33		
Tilt (°)	60		
Rotation (°)	180		

Note

Preliminary photometries.

C1 Mono Spot Wall Small Ø 35



Coated aluminum mount for surface installation (wall)
08.0209.DY



Coated aluminum mount for surface installation (wall)
08.0209.DR



Aluminum Mount for Surface Flush Installation (wall)
08.0231.00



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207



Ø82
⚡

No Trim installation frame for wall mounting
08.0206.00



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable
60.9592



Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186