

### C1 Mono Spot Wall Small Ø 35

03.1205.DY - White



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.


Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location.

#### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Wall
<b>Power (W)</b>	6W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	382		

#### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15
<b>Beam angle C90-270 (°)</b>	15



Beam Angle: 15°

h(m) E(lx) D(m)

1	4198	0.26
2	1050	0.51
3	466	0.77
4	262	1.03
5	168	1.28



Luminous flux luminaire  
382 lm

#### Electrical

<b>Current (mA)</b>	500
<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

#### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	35
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.33		
<b>Tilt (°)</b>	60		
<b>Rotation (°)</b>	180		



C1 Mono Spot Wall Small Ø 35



Coated aluminum mount for surface installation (wall)  
08.0209.DR



Coated aluminum mount for surface installation (wall)  
08.0209.EQ



Coated aluminum mount for surface installation (wall)  
08.0209.ER



Coated aluminum mount for surface installation (wall)  
08.0209.ES



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W  
60.9186



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



No Trim installation frame for wall



Coated aluminum mount for surface installation (wall)



Aluminum Mount for Surface Flush



---

Non dimmable continuous current  
power supply. 15-30W, 220/240V  
-50/60Hz with power current selected  
through adjustable switch. 350mA –  
15W / 400mA – 17W / 450mA – 19W /  
500mA – 22W / 550mA – 24W / 600mA –  
26W / 650mA – 28W / 700mA – 30W no  
regulable  
60.9592