

## Camera 60 Dali Version

### 09.8100.DR.DA - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	993
Lamp category	LED	Mountings	Track
Power (W)	10W	Environment	Indoor
CCT (K)	3000K		
CRI	97		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	9
Beam angle C90-270 (°)	9



Beam Angle: 9°

	h(m)	E(lx)	D(m)
1	24923	0.16	
2	6231	0.32	
3	2769	0.48	
4	1558	0.64	
5	997	0.80	

Luminous flux luminaire  
993 lm

### Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		
Emergency	Without		

### Physical


Color	Anthracite	Spot diameter (mm)	60
Orientation	Adjustable	Length (mm)	111
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		

### Note

Preliminary photometry.



### Certification / Marking



# Camera 60 Dali Version



---

Honeycomb  
08.0175.14