

Camera 60 GA-69 Dali Version

New

09.8113.WA.DA - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	**Net lumen (lm)**	1310
Lamp category	LED	**Mountings**	Track GA
Power (W)	20W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	97		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	34
Beam angle C90-270 (°)	34
UGRL	3
Efficiency (lm/W)	65.5



Luminous flux luminaire
1310 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	4423	0.61
2	1106	1.21
3	491	1.82
4	276	2.42
5	177	3.03

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220-240	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		

Physical

Color	Textured White	**Spot diameter (mm)**	60
Orientation	Adjustable	**Length (mm)**	111
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		

Note

DALI version requires dimmable tracks (please refer to the “Tracks” chapter).

Camera 60 GA-69 Dali Version

Honeycomb
08.0176.14