



Camera 60 GA-69 Dali Version

New

09.8114.WA.DA - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1280 |
| Lamp category | LED | Mountings | Track GA |
| Power (W) | 20W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 97 | | |

Optical

| | |
|------------------------|------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 50 |
| Beam angle C90-270 (°) | 50 |
| UGRL | 3 |
| Efficiency (lm/W) | 64 |



Beam Angle: 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2317 | 0.94 |
| 2 | 579 | 1.89 |
| 3 | 257 | 2.83 |
| 4 | 145 | 3.77 |
| 5 | 93 | 4.72 |

Luminous flux luminaire
1280 lm

Electrical

| | | | |
|----------------|---------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220-240 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|--------------|----------------|--------------------|-----|
| Color | Textured White | Spot diameter (mm) | 60 |
| Orientation | Adjustable | Length (mm) | 111 |
| Weight (kg) | 0.57 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

DALI version requires dimmable tracks (please refer to the "Tracks" chapter).

Camera 60 GA-69 Dali Version



Honeycomb
08.0176.14