

Camera 60 GA-69 Dali Version

New

■ 09.8116.DR.DA - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




Main specifications

Number of heads	1	Net lumen (lm)	1391
Lamp category	LED	Mountings	Track GA
Power (W)	20W	Environment	Indoor dry location
CCT (K)	3500K		
CRI	97		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15
UGRL	3
Efficiency (lm/W)	69.55



Beam Angle: 15°

h(m) E(lx) D(m)

1 16229 0.27

2 4057 0.54

3 1803 0.81

4 1014 1.09

5 649 1.36

Luminous flux luminaire
1391 lm

Electrical



Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	Anthracite	Spot diameter (mm)	60
Orientation	Adjustable	Length (mm)	111
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		

Note

DALI version requires dimmable tracks (please refer to the "Tracks" chapter).



Camera 60 GA-69 Dali Version



Honeycomb
08.0175.14