


Camera 60 GA-69 Non Dimmable

New

09.8117.WA - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1356 |
| Lamp category | LED | Mountings | Track GA |
| Power (W) | 20W | Environment | Indoor dry location |
| CCT (K) | 3500K | | |
| CRI | 97 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 23 |
| Beam angle C90-270 (°) | 23 |



Beam Angle: 23°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 9464 | 0.41 |
| 2 | 2366 | 0.81 |
| 3 | 1052 | 1.22 |
| 4 | 591 | 1.62 |
| 5 | 379 | 2.03 |

Luminous flux luminaire
1356 lm

Electrical

| | | | |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|----------------|--------------------|-----|
| Color | Textured White | Spot diameter (mm) | 60 |
| Orientation | Adjustable | Length (mm) | 111 |
| Weight (kg) | 0.57 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Camera 60 GA-69 Non Dimmable



Honeycomb
08.0176.14