



## Camera 60 GA-69 Non Dimmable

New

## 09.8119.WA - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




## Main specifications

Number of heads	1	Net lumen (lm)	1371
Lamp category	LED	Mountings	Track GA
Power (W)	20W	Environment	Indoor dry location
CCT (K)	3500K		
CRI	97		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	50
Beam angle C90-270 (°)	50
UGRL	18
Efficiency (lm/W)	42.84



Beam Angle: 50°

h(m)	E(lx)	D(m)
1	2481	0.94
2	620	1.89
3	276	2.83
4	155	3.77
5	99	4.72

Luminous flux luminaire  
1371 lm

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

## Physical

Color	Textured White	Spot diameter (mm)	60
Orientation	Adjustable	Length (mm)	111
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		

## Camera 60 GA-69 Non Dimmable



---

Honeycomb  
08.0176.14