


Camera 60 GA-69 Potenciometer

New

09.8110.DR.PC - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 711 |
| Lamp category | LED | Mountings | Track GA |
| Power (W) | 13W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 97 | | |

Optical

| | |
|------------------------|------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Super spot |
| Beam angle (°) | 9 |
| Beam angle C90-270 (°) | 9 |



| | | |
|-------------|------|------------|
| Beam Angle: | 9° | |
| | h(m) | E(lx) D(m) |
| | 1 | 22666 0.16 |
| | 2 | 5667 0.32 |
| | 3 | 2518 0.48 |
| | 4 | 1417 0.63 |
| | 5 | 907 0.79 |

Luminous flux luminaire
711 lm

Electrical

| | | | |
|----------------|-----------------|------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmer on board | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|-----|
| Color | Anthracite | Spot diameter (mm) | 60 |
| Orientation | Adjustable | Length (mm) | 111 |
| Weight (kg) | 0.57 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Camera 60 GA-69 Potenciómeter



Honeycomb
08.0175.14