



## Camera 60 Potenciometer

New

### 09.8103.WA.PC - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.




### Main specifications

Number of heads	1	Net lumen (lm)	1310
Lamp category	LED	Mountings	Track
Power (W)	20W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	97		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	34
Beam angle C90-270 (°)	34
UGRL	3
Efficiency (lm/W)	65.5



Beam Angle: 34°

	h(m)	E(lx)	D(m)
1	4423	0.61	
2	1106	1.21	
3	491	1.82	
4	276	2.42	
5	177	3.03	

Luminous flux luminaire  
1310 lm

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Physical

Color	Textured White	Spot diameter (mm)	60
Orientation	Adjustable	Length (mm)	111
Weight (kg)	0.57	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

## Camera 60 Potenciometer



---

Honeycomb  
08.0176.14