


## Camera 90 Casambi integrated

New

### 09.8200.DR.CB - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1275                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track               |
| <b>Power (W)</b>       | 20W   | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 97    |                       |                     |

### Optical

|                               |            |
|-------------------------------|------------|
| <b>Lighting type</b>          | Direct     |
| <b>LED type</b>               | LED array  |
| <b>Light distribution</b>     | Symmetric  |
| <b>Optical type</b>           | Super spot |
| <b>Beam angle (°)</b>         | 11         |
| <b>Beam angle C90-270 (°)</b> | 11         |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 11°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 26740        | 0.20        |  |
| 2                  | 6685         | 0.39        |  |
| 3                  | 2971         | 0.59        |  |
| 4                  | 1671         | 0.78        |  |
| 5                  | 1070         | 0.98        |  |

Luminous flux luminaire  
1275 lm

### Electrical

|                       |            |                         |   |
|-----------------------|------------|-------------------------|---|
| <b>Frequency (Hz)</b> | 50/60      | <b>Insulation class</b> | I |
| <b>Dimmable</b>       | Yes        |                         |   |
| <b>Driver</b>         | Integrated |                         |   |
| <b>Driver type</b>    | Dimmable   |                         |   |
|                       | Casambi    |                         |   |
| <b>Emergency</b>      | Without    |                         |   |

### Physical

|                     |            |                           |     |
|---------------------|------------|---------------------------|-----|
| <b>Color</b>        | Anthracite | <b>Spot diameter (mm)</b> | 90  |
| <b>Orientation</b>  | Adjustable | <b>Length (mm)</b>        | 131 |
| <b>Weight (kg)</b>  | 0.75       |                           |     |
| <b>Tilt (°)</b>     | 90         |                           |     |
| <b>Rotation (°)</b> | 360        |                           |     |

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

## Camera 90 Casambi integrated



---

Honeycomb  
08.0177.14