

## Camera 90 Casambi integrated

New

### 09.8205.WA.CB - Textured White


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1365                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 20W   | Environment    | Indoor dry location |
| CCT (K)         | 3500K |                |                     |
| CRI             | 97    |                |                     |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | LED array  |
| Light distribution     | Symmetric  |
| Optical type           | Super spot |
| Beam angle (°)         | 11         |
| Beam angle C90-270 (°) | 11         |
| UGRL                   | 3          |
| Efficiency (lm/W)      | 68.25      |



Beam Angle: 11°

h(m) E(lx) D(m)

1 28632 0.20

2 7158 0.39

3 3181 0.59

4 1789 0.78

5 1145 0.98

Luminous flux luminaire  
1365 lm

### Electrical



|                |                     |                  |         |
|----------------|---------------------|------------------|---------|
| Frequency (Hz) | 50/60               | Emergency        | Without |
| Voltage (V)    | 220-240             | Insulation class | I       |
| Dimmable       | Yes                 |                  |         |
| Driver         | Integrated          |                  |         |
| Driver type    | Dimmable<br>Casambi |                  |         |

### Physical

|              |                |                    |     |
|--------------|----------------|--------------------|-----|
| Color        | Textured White | Spot diameter (mm) | 90  |
| Orientation  | Adjustable     | Length (mm)        | 131 |
| Weight (kg)  | 0.75           |                    |     |
| Tilt (°)     | 90             |                    |     |
| Rotation (°) | 360            |                    |     |

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



## Camera 90 Casambi integrated



---

Honeycomb  
08.0177.14