


## Camera 90 Casambi integrated

New

09.8209.WA.CB - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.




### Main specifications

<b>Number of heads</b>	1	<b>Mountings</b>	Track
<b>Lamp category</b>	LED	<b>Environment</b>	Indoor dry location
<b>Power (W)</b>	32W		
<b>CCT (K)</b>	3500K		
<b>CRI</b>	97		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	56
<b>Beam angle C90-270 (°)</b>	56



<b>Beam Angle:</b>	55°	
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2681	1.05
2	670	2.09
3	298	3.14
4	168	4.19
5	107	5.24

Luminous flux luminaire  
2367 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable		
	Casambi		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Textured White	<b>Spot diameter (mm)</b>	90
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	131
<b>Weight (kg)</b>	0.75		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.  
Preliminary photometry.

## Camera 90 Casambi integrated



---

Honeycomb  
08.0178.14