


## Certification / Marking



## Camera 90 Dali Version

### 09.8200.DR.DA - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.

## Main specifications

Number of heads	1	Net lumen (lm)	1723
Lamp category	LED	Mountings	Track
Power (W)	19W	Environment	Indoor
CCT (K)	3000K		
CRI	97		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle: 11°

	h(m)	E(lx)	D(m)
1	31662	0.19	
2	7916	0.38	
3	3518	0.57	
4	1979	0.76	
5	1266	0.94	

Luminous flux luminaire  
1723 lm

## Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		
Emergency	Without		

## Physical

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		

## Note

Preliminary photometry.

# Camera 90 Dali Version



---

Honeycomb  
08.0177.14