



## Camera 90 Dali Version

■ 09.8209.DR.DA - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Mountings	Track
Lamp category	LED	Environment	Indoor
Power (W)	29W		
CCT (K)	3500K		
CRI	97		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle: 55°

	h(m)	E(lx)	D(m)
1	2681	1.05	
2	670	2.09	
3	298	3.14	
4	168	4.19	
5	107	5.24	

Luminous flux luminaire  
2367 lm



### Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		
Emergency	Without		


### Physical

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		

### Note

Preliminary photometry.

### Certification / Marking



# Camera 90 Dali Version



---

Honeycomb  
08.0178.14