


## Camera 90 GA-69 Dali Version

■ 09.8213.DR.DA - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2298
<b>Lamp category</b>	LED	<b>Mountings</b>	Track GA
<b>Power (W)</b>	32W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	97		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	37
<b>Beam angle C90-270 (°)</b>	37



Beam Angle: 37°

	h(m)	E(lx)	D(m)
1	4871	0.67	
2	1218	1.35	
3	541	2.02	
4	304	2.69	
5	195	3.37	

Luminous flux luminaire  
2298 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic dimmable DALI		
<b>Emergency</b>	Without		


### Physical

<b>Color</b>	Anthracite	<b>Spot diameter (mm)</b>	90
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	131
<b>Weight (kg)</b>	0.75		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

DALI version requires dimmable tracks (please refer to the "Tracks" chapter). Preliminary photometry.

### Certification / Marking



## Camera 90 GA-69 Dali Version



---

Honeycomb  
08.0178.14