



## Camera 90 GA-69 Non Dimmable

New

09.8216.WA - Textured White

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2290
<b>Lamp category</b>	LED	<b>Mountings</b>	Track GA
<b>Power (W)</b>	32W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3500K		
<b>CRI</b>	97		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	14
<b>Beam angle C90-270 (°)</b>	14



Beam Angle: 14°

h(m) E(lx) D(m)

1 32766 0.25

2 8192 0.49

3 3641 0.74

4 2048 0.99

5 1311 1.24

Luminous flux luminaire  
2290 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Textured White	<b>Spot diameter (mm)</b>	90
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	131
<b>Weight (kg)</b>	0.75		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

## Camera 90 GA-69 Non Dimmable



---

Honeycomb  
08.0177.14