



Camera 90 GA-69 Non Dimmable



09.8219.DR - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated.


Main specifications

Number of heads	1
Lamp category	LED
Power (W)	32W
CCT (K)	3500K
CRI	97

2199 Net lumen (lm) Mountings Track GA Indoor dry location Environment

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	56
Beam angle C90-270 (°)	56
UGRL	18
Efficiency (lm/W)	68.72



Luminous flux luminaire 2367 lm

Bea	m Angle:	55°
h(m)) E(lx)	D(m)
1	2681	1.05
2	670	2.09
3	298	3.14
4	168	4.19
5	107	5.24

	121
131	6 36 48





Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	No		
Driver	Integrated		

Non Dimmable

Physical

Driver type

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75	_	
Tilt (°)	90		
Rotation (°)	360		

Note

Preliminary photometry.

Camera 90 GA-69 Non Dimmable



Honeycomb 08.0178.14