



## Camera 90 Non Dimmable

New

### 09.8202.DR - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.


#### Main specifications

Number of heads	1	Net lumen (lm)	2298
Lamp category	LED	Mountings	Track
Power (W)	32W	Environment	Indoor
CCT (K)	3000K		
CRI	97		



#### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	9583	0.44
2	2396	0.88
3	1065	1.33
4	599	1.77
5	383	2.21

Luminous flux luminaire  
2298 lm



#### Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

#### Physical

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		

#### Note

Preliminary photometry.



## Camera 90 Non Dimmable



---

Honeycomb  
08.0178.14