


Camera 90 Non Dimmable

09.8205.DR - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.




Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1775 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 13W | Environment | Indoor |
| CCT (K) | 3500K | | |
| CRI | 97 | | |

Optical

| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Super spot |
| Beam angle (°) | 11 |
| Beam angle C90-270 (°) | 11 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 11° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 32611 | 0.19 | |
| 2 | 8153 | 0.38 | |
| 3 | 3623 | 0.57 | |
| 4 | 2038 | 0.76 | |
| 5 | 1304 | 0.94 | |

Luminous flux luminaire
1775 lm

Electrical

| | | | |
|-----------------------|------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |
| Emergency | Without | | |


Physical

| | | | |
|---------------------|------------|---------------------------|-----|
| Color | Anthracite | Spot diameter (mm) | 90 |
| Orientation | Adjustable | Length (mm) | 131 |
| Weight (kg) | 0.75 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Preliminary photometry.

Certification / Marking



Camera 90 Non Dimmable



Honeycomb
08.0177.14