



Camera 90 Non Dimmable

New

09.8205.WA - Textured White


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.

Main specifications

Number of heads	1	Net lumen (lm)	1365
Lamp category	LED	Mountings	Track
Power (W)	20W	Environment	Indoor dry location
CCT (K)	3500K		
CRI	97		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	11
Beam angle C90-270 (°)	11
UGRL	3
Efficiency (lm/W)	68.25



Beam Angle: 11°

	h(m)	E(lx)	D(m)
--	------	-------	------

1	28632	0.20
---	-------	------

2	7158	0.39
---	------	------

3	3181	0.59
---	------	------

4	1789	0.78
---	------	------

5	1145	0.98
---	------	------



Luminous flux luminaire
1365 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Textured White	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		



Camera 90 Non Dimmable



Honeycomb
08.0177.14