


Camera 90 Non Dimmable

New

09.8208.DR - Anthracite

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.




Main specifications

Number of heads	1	Net lumen (lm)	2276
Lamp category	LED	Mountings	Track
Power (W)	32W	Environment	Indoor dry location
CCT (K)	3500K		
CRI	97		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	43
Beam angle C90-270 (°)	43



Beam Angle:	43°		
h(m)	E(lx)	D(m)	
1	5258	0.78	
2	1315	1.56	
3	584	2.34	
4	329	3.12	
5	210	3.90	

Luminous flux luminaire
2276 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		

Camera 90 Non Dimmable



Honeycomb
08.0178.14