

## Camera 90 Potenciometer

☐ **09.8202.WA.PC - Textured White**

Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2298
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	32W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	97		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	25
<b>Beam angle C90-270 (°)</b>	25



Beam Angle: 25°		
h(m)	E(lx)	D(m)
1	9583	0.44
2	2396	0.88
3	1065	1.33
4	599	1.77
5	383	2.21

Luminous flux luminaire  
2298 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		
<b>Emergency</b>	Without		


### Physical

<b>Color</b>	Textured White	<b>Spot diameter (mm)</b>	90
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	131
<b>Weight (kg)</b>	0.75		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Preliminary photometry.

### Certification / Marking



## Camera 90 Potenciometer



---

Honeycomb  
08.0178.14