

### Camera 90 Potenciometer

New

#### 09.8203.DR.PC - Anthracite


Spotlight to be installed on 3-phase track with LED light source. 220- 240V, 50-60Hz power supply integrated. To be used with The Tracking Power profiles.

#### Main specifications

Number of heads	1	Net lumen (lm)	2066
Lamp category	LED	Mountings	Track
Power (W)	32W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	97		

#### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	43
Beam angle C90-270 (°)	43
UGRL	4
Efficiency (lm/W)	64.56



Beam Angle: 43°

	h(m)	E(lx)	D(m)
1	4772	0.78	
2	1193	1.56	
3	530	2.34	
4	298	3.12	
5	191	3.90	




Luminous flux luminaire  
2066 lm

#### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220-240	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

#### Physical

Color	Anthracite	Spot diameter (mm)	90
Orientation	Adjustable	Length (mm)	131
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		



## Camera 90 Potenciometer



---

Honeycomb  
08.0178.14