


■ 03.3520.02 - Grey

Recessed 12V lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1	Mountings	Ceiling recessed
Lamp category	LED retrofit	Environment	Indoor dry location
CCT (K)	3000K		
CRI	100		
Net lumen (lm)	804		

Lighting type	Direct
Lamp type	QR-111
Light distribution	Symmetric
Optical type	Spot



Luminous flux luminaire
978 lm

Beam Angle:	19°	
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	3496	0.33
2	874	0.67
3	388	1.00
4	218	1.34
5	140	1.67

Electrical

Frequency (Hz)	50/60	Emergency	Without
Lamp holder	G53	Insulation class	III
Dimmable	No		
Driver	Remote excluded		
Driver type	Electronic 12V		

Color	Grey
Orientation	Adjustable
Recessed depth (mm)	220
Weight (kg)	0.55
Rotation (°)	40

Compass Adjustable Ø 162



Hot Light
08.8932.69




Red filter
08.8932.67.OD




U.V. filter
08.8932.98.OD



I.R. filter
08.8933.68



Sky blue filter
08.8932.65.OD



Amber filter
08.8932.66.OD



Daylight filter
08.8932.DL



Elliptical light distribution lens
08.8930.68




Flood lens made in press glass
08.8931.68



Honeycomb
08.8036.14



Neodimium
08.8932.ND



Blue filter
08.8932.64.OD



Cold light filter
08.8932.CL



Screening cylinder
08.8034.14