


Certification / Marking



Compass Adjustable Ø162

■ 03.3520.14 - Matt black


Recessed 12V halogen lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1	Net lumen (lm)	804
Lamp category	Halogen	Mountings	Ceiling recessed
Power (W)	100W Max.	Environment	Indoor
CCT (K)	3000K		
CRI	100		

Optical

Lamp type	QR-111
Light distribution	Symmetric
Optical type	Spot



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	3496	0.33
2	874	0.67
3	388	1.00
4	218	1.34
5	140	1.67

Luminous flux luminaire
978 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Lamp holder	G53	Insulation class	III
Dimmable	No		
Driver	Remote		
Driver type	Electronic		

Physical

Color	Matt black
Orientation	Adjustable
Recessed depth (mm)	220
Weight (kg)	0.55
Rotation (°)	40

Compass Adjustable Ø162



Screening cylinder
08.8034.14



Honeycomb
08.8036.14




Elliptical light distribution lens
08.8930.68




Flood lens made in press glass
08.8931.68



Blue filter
08.8932.64.OD



Sky blue filter
08.8932.65.OD



Amber filter
08.8932.66.OD



Red filter
08.8932.67.OD



U.V. filter
08.8932.98.OD



I.R. filter
08.8933.68



Hot Light
08.8932.69



Cold light filter
08.8932.CL



Daylight filter
08.8932.DL



Neodimium
08.8932.ND