

## Compass Adjustable Ø162

■ 03.3526.02 - Grey

Metal halide lamp recessed downlight. Remote control gear not included


Metal halide lamp recessed downlight. Remote control gear not included

### Main specifications

|                 |              |                |                  |
|-----------------|--------------|----------------|------------------|
| Number of heads | 1            | Net lumen (lm) | 11074            |
| Lamp category   | Metal halide | Mountings      | Ceiling recessed |
| Power (W)       | 150W Max.    | Environment    | Indoor           |
| CCT (K)         | 3000K        |                |                  |
| CRI             | 85           |                |                  |

### Optical

|                        |            |
|------------------------|------------|
| Lamp type              | HIT-CRI    |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 39         |
| Beam angle C90-270 (°) | 39         |



Beam Angle: 39°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 4558  | 0.71 |
| 2    | 1140  | 1.42 |
| 3    | 506   | 2.13 |
| 4    | 285   | 2.85 |
| 5    | 182   | 3.56 |

Luminous flux luminaire  
3400 lm

### Electrical

|                  |         |
|------------------|---------|
| Frequency (Hz)   | 50/60   |
| Lamp holder      | G12     |
| Emergency        | Without |
| Insulation class | I       |

### Physical

|                     |            |
|---------------------|------------|
| Color               | Grey       |
| Orientation         | Adjustable |
| Recessed depth (mm) | 220        |
| Weight (kg)         | 0.71       |
| Rotation (°)        | 40         |

### Certification / Marking

