

## Compass Box Small 1L

■ 03.2600.TK - Teak




Surface spotlight to be installed on ceiling/wall. Electronic transformer integrated 220/240V – 12V, 50/60Hz. The intensity of the lighting may be adjusted via leading and trail edge modulation.

## Main specifications

Number of heads	1	Mountings	Ceiling surface
Lamp category	LED retrofit	Environment	Indoor dry location
CCT (K)	3100K		
CRI	100		
Net lumen (lm)	357		

## Optical

Lamp type	QR-CBC 51
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle: 10°

h(m) E(lx) D(m)

1 5000 0.17

2 1250 0.34

3 556 0.51

4 313 0.69

5 200 0.86



Luminous flux luminaire  
357 lm

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Lamp holder	GX5.3	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic 12V		

## Physical

Color	Teak
Orientation	Adjustable
Weight (kg)	1
Tilt (°)	20



## Compass Box Small 1L



---

Honeycomb  
08.8196.14



---

Screening cylinder  
08.8238.14