

## Compass Box Small 1L

■ 03.2631.TKA - Teak

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 591                 |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 6.2W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 80    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 27        |



Beam Angle: 26°

h(m) E(lx) D(m)

1 1326 0.47

2 332 0.93

3 147 1.40

4 83 1.87

5 53 2.34

Luminous flux luminaire  
591 lm (EXTREME CUT OFF)

## Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

## Physical

|             |            |
|-------------|------------|
| Color       | Teak       |
| Orientation | Adjustable |
| Weight (kg) | 1          |
| Tilt (°)    | 20         |

