

## Compass Box Small 4L

■ 03.2642.29A - Anodized Aluminium

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 4     | Net lumen (lm) | 580                 |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 6.2W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 80    |                |                     |

## Optical

|                        |            |
|------------------------|------------|
| LED type               | LED array  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 59         |
| Beam angle C90-270 (°) | 60         |



Beam Angle: 59°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 632   | 1.14 |
| 2    | 158   | 2.28 |
| 3    | 70    | 3.42 |
| 4    | 39    | 4.56 |
| 5    | 25    | 5.70 |

Luminous flux luminaire  
580 lm (EXTREME CUT OFF)

## Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

## Physical

|             |                       |
|-------------|-----------------------|
| Color       | Anodized<br>Aluminium |
| Orientation | Adjustable            |
| Weight (kg) | 3                     |
| Tilt (°)    | 20                    |

