

## Direct Light Tube 1500 mm

■ 03.8402.14 - Black


Diffused LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile. The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is completed by...

Diffused LED light module to be installed in the Infra-Structure Episode 2.

Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile.

The Light Tubes are only fed by one of the ends and do not communicate current through the other end.

Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2329
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	35.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	150
<b>Beam angle C90-270 (°)</b>	106




Beam Angle: 150°

h(m)	E(lx)	D(m)
1	571	7.49
2	143	14.98
3	63	22.47
4	36	29.96
5	23	37.45

Luminous flux luminaire  
2329 lm

### Certification / Marking



### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Length (mm)</b>	1500

## Direct Light Tube 1500 mm



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919



LED Power Supply Source for remote installation. 48V/185W. 100/240 Vac  
60.9024



LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170



Casambi Broadcast. Remote Installation  
60.9392



0-10V, 1-10V, DALI and PUSH interface  
60.9391