

## Direct Light Tube 900 mm

New

### ■ 03.8403.14 - Black


Diffused LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile. The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is completed by...

Diffused LED light module to be installed in the Infra-Structure Episode 2.

Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile.

The Light Tubes are only fed by one of the ends and do not communicate current through the other end.

Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	1515
<b>Power (W)</b>	22W	<b>Mountings</b>	Ceiling surface
<b>System power (W)</b>	23	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	150
<b>Beam angle C90-270 (°)</b>	106
<b>Efficiency (lm/W)</b>	65.87



Beam Angle: 150°

h(m)	E(lx)	D(m)
1	371	7.49
2	93	14.98
3	41	22.47
4	23	29.96
5	15	37.45

Luminous flux luminaire  
1515 lm



### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.7
<b>Length (mm)</b>	900
<b>Lifespan (L70 B10)</b>	L80B50

## Direct Light Tube 900 mm



---

LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170

DALI 12-48V Dimmer  
60.9678

0/1-10V & Push 12-48V Dimmer  
60.9395



---

Casambi Controller 220-240V. Remote Installation  
60.9392

LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)  
60.9607

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919