



Diversion Down + Spots. L 1000 mm

09.8020.CZ - Bronze



Electro-mechanical profile for indoor application with integrated direct linear light element and space for two spots, for surface or suspended installation. With lengths varying from 1 to 2.5m (distance between ball joint centers). Fixation by fed suspension kit and suspended by a joint. Power kit and mechanical joint must be ordered separately. System controlled by...

Electro-mechanical profile for indoor application with integrated direct linear light element and space for two spots, for surface or suspended installation. With lengths varying from 1 to 2.5m (distance between ball joint centers). Fixation by fed suspension kit and suspended by a joint. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included. For single profile structures, suspended version, balance the spot to avoid profile tilting.




Main specifications

Lamp category	LED	Mountings	Surface and suspension
Power (W)	11W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	325		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	54
Beam angle C90-270 (°)	102
Efficiency (lm/W)	30



Beam Angle: 54°

h(m)	E(lx)	D(m)
1	219	1.01
2	55	2.02
3	24	3.03
4	14	4.04
5	9	5.06

Luminous flux luminaire
325 lm



Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Bronze
Orientation	Fixed
Weight (kg)	0.56
Length (mm)	1000

Note

Max. 2 spots not included.

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

In the case of the version without Spots, drivers with higher switching frequency, up to 2Khz, can be used.

The profile's length measurement corresponds to the distance between the centers of the suspension joints. To install a profile of length L, the distance between joints coincides with the indicated measurement L, but the profile is a few centimeters smaller.

Diversion Down + Spots. L 1000 mm



Feed recessed joint. 24V
 06.5304.CZ



Suspension feed box for surface
 installation. 24V. Driver included DALI /
 57W
 06.5314.CZ



Surface feed box for ceiling
 installation. 24V. Driver included DALI /
 57W
 06.5315.CZ



24V Remote power supply. Dimmable
 through 1/10V protocol or Non
 Dimmable. 57W 220/240V
 60.9361



24V Remote power supply. Dimmable
 through DALI protocol. 120W 110/240V
 60.9426



Surface feed box for ceiling
 installation. 24V. Driver included 1-10V
 / 57W
 06.5312.CZ



Suspension feed box for surface
 installation. 24V. Driver included
 Casambi / 57W
 06.5311.CZ



24V Remote power supply. Dimmable
 through 1/10V protocol. 120W 110/240V
 60.9416



Surface feed box for ceiling
 installation. 24V. Driver included
 CASAMBI / 57W
 06.5313.CZ



Feed recessed joint rose. 24V.
06.5306.CZ



Recessed/surface joint
06.5305.CZ



Suspension joint for surface
installation
06.5303.CZ



Suspension feed box for surface
installation. 24V. Driver included 1-10V
/ 57W
06.5310.CZ



Suspension joint
06.5301.CZ



Feed suspension joint. 24V
06.5300.CZ



Feed suspension joint with rose for
recessing. 24V
06.5302.CZ



Casambi Controller 220-240V. Remote
Installation
60.9392